Active Clamp Forward Converter

Input: 36-72V (Nominal 48V)
Output: 12V, 8.33A, 100W



Auxiliary Power Supply



DESCRIPTION OF NODE NAMES:
5V_sb = 5V standby (external input) required for external shutdown
comp = comp pin of PWM controller chip (IC6: TL2843)
cs = Current sense
cs_unfilt = Current sense (unfiltered)
csb = Current-share bus (connect to csb of other DC/DC)
GND_I = Input-side (primary-side) ground
GND_I = Output-side (secondary-side) ground
ipk = Peak current value (used for ocp)
mid = Node between main and clamp MOSFETs
ocp = Over-current protection
ovp = Over-voltage protection (power off when Vout>14.4V)
otp = Over-temperature protection
pwm1 = PWM pulses for main MOSFET
pwm2 = PWM pulses for clamp MOSFET
sd_o = Shutdown referenced to o/p side gnd (external signal, 5V active high)
sd_i = Shutdown referenced to i/p side gnd (external signal, 5V active high)
ss = Soft-start capacitor node
sync = Synchronisation (external signal)
test_ocp = Test node for OCP (short to gnd_i to simulate over-current)
test_otp1 = Test node for OTP #1 (short to gnd_i to simulate over-temperature)
test_otp2 = Test node for OTP #2 (short to gnd_i to simulate over-temperature)
test_ovp = Test node for OVP (short to gnd_o to simulate over-voltage)
uvlo = Under-voltage lockout (power off when Vin<36V)
va = Input voltage to isolation amplifier (IC14: ACPL-C87B)
vref_o = Ref. voltage of sec-side controller (IC12/IC13: LM4041 on GND_O)



PWM Controller and MOSFET Driver



LIST OF TEST POINTS:
TP1: Vout
TP2: Vcc
TP3: Vin
TP4: +5V
TP5: GND_I
TP6: GND_O
TP7: GND_I
TP8: uvlo
TP9: ocp
TP10: pwm
TP11: comp
TP12: GND_I
TP13: otp2
TP14: otp1
TP15: sd_o
TP16: ovp
TP17: csb
TP18: sd_i
J4 (pin-1): L_pin9
J5 (pin-1): aux
J6 (pin-1): mid
J7 (pin-1): L_pin12
J8 (pin-1): cs
J11 (pin-1): hin
J12 (pin-1): pwm1
J13 (pin-1): lin
J14 (pin-1): pwm2

Protection Circuits



Output Voltage Sensing and Loop Compensation #1



Loop Compensation #2



MOUNTING HOLES:
B1 B2 B3 B4
FIDUCIALS:
FTG1 FTG2 FTG3

Project/Equipment	-
Document	R2E Active Clamp Forward DC/DC 12V, 8.33A, 100W
Designer	Yves Thurel, Lalit Patnaik
Drawn by	Lalit Patnaik — XX/XX/XXXX
Check.by	- — -
Last Mod.	- — 22/10/2020
File	R2E-Active-Clamp-Forward-DC-DC-v1.2-Tested-at-Co60-Oct-2020.SchDoc
Print Date	22/10/2020 11:56:14 — Sheet - of -
European Organization for Nuclear Research, CH-1211 Genève 23 - Switzerland	EDA-XXXXX-VX-X — Size A3 — Rev -

TE-EPC/BE-CO
RaToPUS 12V DC/DC